

You want to learn more about us?

Feel free to ask for a meeting on our premises.
Detailed information on the company and on
our product range is also available on-line at
www.huerner.de



HÜRNER
S C H W E I S S T E C H N I K

HÜRNER Schweisstechnik GmbH

Technologie Straße
35325 Mücke

GERMANY

Ph +49 6401 9127 0

E-Mail: op@huerner.de
Internet: www.huerner.de

HÜRNER Welding Technology NZ Ltd

12 Croskery Road
Papakura
Auckland 2110
NEW ZEALAND

Ph +64 9 299 3640
Fx +64 9 299 3740


E-Mail: admin@huerner.co.nz
Internet: www.huerner.co.nz

HÜRNER Schweisstechnik Gulf L.L.C

Damascus Street, Al Qusais 4
DUBAI
P.O.Box 233586
UNITED ARAB EMIRATES

Ph +971 4 2584886
Fx +971 4 2584887
E-Mail: sales@hurnergulf.com
Internet: www.hurnergulf.com

10.2025



Model Sample

HÜRNER WhiteLine HWT 500 CS

EN


HÜRNER
S C H W E I S S T E C H N I K

HÜRNER HWT 500 CS characteristics


P/N	409-000-...
HWT 500 CS w/ narrow aluminum master clamps, metric	-000
HWT 500 CS w/ narrow aluminum master clamps, IPS	-001
Technical specs	
Input voltage	3 ph., PE, 400 V AC
Frequency	50/60 Hz
Overall rated power	13,6 kW
Heating element rated power	8 kW
Facing tool rated power	2,2 kW
Servomotor rated power	3,4 kW
Changeover time	2 Sec.
Compressed air	min. 6 bar 87 PSI
Dimensions, weights	
Dimensions (W × D × H)	approx. 1500 × 2500 × 1700 mm
Weight inclusive of master clamps	approx. 1490 kg
Approvals, quality, ingress protection	CE, ISO 9001:2015, WEEE Reg. No. DE 74849106, RoHS-compliant. The air quality must be at least equal to the “general factory air”, (2:4:2) classified according to ISO 8573-1:2010
Accessories	User’s manual, operator ID card, tools

Operating characteristics		
Heating element temperature range	max. 290 °C max. 555 °F	
Force rating	max. 20,000 N	
Ambient temperature (operation)	5 °C thru +40 °C 41 °F thru 104 °F	
Ambient temperature (storage)	−10 °C thru +70 °C 15 °F thru 160 °F	
Operating range w/ straight pipe, segments	160–500 mm 6″ –20″ IPS	
Operating range w/ Tees, crosspieces, Ys ¹⁾	160–500 mm 6″ –20″ IPS	
Optional components		
Label tag printer	P/N	200-230-326
Tray for label tag printer	P/N	404-810-103
Replacement blade	P/N	200-600-099
Handheld scanner (QR-Code)	P/N	216-030-267
Welding neck support, metric	P/N	409-400-000
Welding neck support, IPS	P/N	409-410-000
Additional servo-operated Cylinder	P/N	409-266-000
Preheating-unit	P/N	409-153-000


Also available as an option



Clamps for Tees / crosspieces²⁾



Clamps for Ys (60 deg.)²⁾



Welding neck support (two-piece)



Preheating-unit

Technical changes reserved.

¹⁾ requires optional clamps for Tees / crosspieces and/or clamps for Ys (60 deg.)
²⁾ under construction

HÜRNER HWT 500 CS servo-operated workshop system for manufacturing PE, PE 100 RC, PP, and PVC-U, PVC-C pipes, segmented bends, and fittings, fitted with narrow aluminum master clamps.

The design of the machine is such that pipes and segments up to O.D. 500 mm / 20” with any SDR ratio up to SDR 9 can be processed.

The system was developed under the machinery directive 2006/42/EC as amended and is set on a welded and bolted, totally heavy-duty support frame resistant to warping by design. Both the movable carriage of the system and the console carrying the heating element and the facing tool travel on precision-engineered, heavy load-bearing trapeze-shaped guides constructed with smoothly travelling runner blocks.

A pneumatic cylinder will remove the heating element from in-between the components in no time, enabling change-over in as short as 2 seconds. The facing tool assembly, too, is inserted and removed automatically.

The swiveling master clamps on both sides can be rotated by up to 2 × 22.5 deg. and also feature horizontal and vertical adjustability, to allow for compensating any misalignments. The facing tool has a rugged chain drive mechanism and is inserted and fastened between the component butts as easy as ABC thanks to a gas-pressure cylinder.

The heating element temperature control and the application of the welding force precision-controlled by a servomotor are performed in compliance with the standard applicable to the operation (DVS, UNI, WIS, NEN, etc.).


All welding parameters critical for a high-quality and reproducible welded joint, it goes without saying, are monitored for the entire welding process and saved to one of the 10,000 welding reports the system memory holds.

In its standard delivery, the machine features a high-resolution color display touchscreen. This device allows entering and displaying both all required component parameters and the needed traceability information.

All components are covered by the 12-month HÜRNER warranty.



Welding Cockpit



Horizontal adjustability of both carriages



Vertical adjustability



Height adjustable pipe support



Tag printer and label tags

Immediate quality labeling of every welded joint is possible with the optional dedicated tag printer that delivers an abrasion-proof plastic sticker which can be used as a label on the fitting or joint.

HÜRNER HWT 500 CS control system specs

Automatic data logging	10,000 welding operations
Data input	Touchscreen, RFID reader, scanner (optionally)
System self-monitoring	System check, Computerized maintenance management including logging
Welding monitoring system	Welding forces, welding times, ambient temperature, memory control, heating element temperature
Standard-compliant ISO 12176 traceability	Commission number with 32 alphanumeric characters, ISO-compliant RFID welder ID code, additional (user-defined) data alphanumeric characters, ISO-compliant pipe parameters, fitting parameters, pipe length, installing company, joint number, inventory number, display of maintaining company; supported welding standards DVS, WIS, SEDIGAS, UNI, NEN, others upon request
Data download with print menu	USB port (USB A) for data transfer as PDF abstract or extended report to USB stick or (optional) label tag printer, incl. tag printer menu; transfer also possible in the HÜRNER DataWork Professional database format
Working languages	DE, EN, FR, NL, IT, others upon request